

402404

HORIZON MEDIUM 02 Designed by PAOLO VILLA

Applique of rectangular shape for outdoor installation on a façade/wall, with double light emission (up/down). Phospho-chromatised and polyester powder coated die-cast copperfree aluminium body, tempered frosted safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 42 mid-power CREE XH-G LED. IP65 rating.

		350 mm		32 mm
120 mm	•		•	
	ŀ	354 mm		36 mm

Technical features



Technical data

Wattage	23 WATT	
IP Rating	IP65	
IK Rating	IK08	
Material	High corrosion resistance die-cast copper-free aluminum body and fixing arms	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	NR. 42 x CREE "XH-G" LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Gross weight	3,00 Kg	
-		



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)				
3000°K warm-white							
mid-power led	bi-directional diffused	1.204	52,35				
* Other light colors available on request: Neutral-white							

Anthracite Grey RAL 7016

Finish color options:

Textured Grey RAL 9006

.

Matt Black (on request)